

CLASSIFICATION 類別		TIMER 定時器			
MODEL 型號		ALST8	ALC18	ALC18-E	TM-26
APPEARANCE 外觀					
CONTACT CAPACITY 觸點容量		AC220V 16A	AC220V 16A	AC220V 16A	AC220V 16A
FULL TIMING RANGE 時間範圍		7min/7分	20min/20分	20min/20分	24h/24小时
CONTACT RESISTANCE 接觸電阻		$\leq 50m\Omega$	$\leq 50m\Omega$	$\leq 50m\Omega$	$\leq 50m\Omega$
INSULATION RESISTANCE 絕緣電阻		$\geq 100M\Omega$	$\geq 100M\Omega$	$\geq 100M\Omega$	$\geq 100M\Omega$
RATED VOLTAGE 額定電壓		110, 230V AC	110, 230V AC	110, 230V AC	110, 230V AC
LIFE 壽命	ELECTRICAL 電氣	10^5 times/ 10^5 次	10^5 times/ 10^5 次	10^5 times/ 10^5 次	10^5 times/ 10^5 次
	MECHANICAL 機械	10^7 times/ 10^7 次	10^7 times/ 10^7 次	10^7 times/ 10^7 次	10^7 times/ 10^7 次
AMBIENT TEMPERATURE 環境溫度		-20°C~+55°C	-20°C~+55°C	-20°C~+55°C	-20°C~+55°C
DIMENSIONS(mm) 外形尺寸					
MINIMUM SETTING UNIT 最小設定單位		0.5Minutes 0.5分	0.5Minutes 0.5分	0.5Minutes 0.5分	15Minutes 15分
SET-UP TIMES 設定次數		1M,1.5M,2M,2.5M, 3M,3.5M,4M,4.5M,5M, 5.5M,6M,6.5M,7M	0.5M, 5M, 10M, 15M, 20M	0.5M, 5M, 10M, 15M, 20M	96times 96次
CONSUMED POWER 消耗功率 MAX		1VA	5VA stand by mode 1VA	5VA	1VA